



**BRAZED PLATE LIQUID-TO-LIQUID
HEAT EXCHANGERS**

PRODUCT DESCRIPTION

Boyd's brazed-plate heat exchangers are unsurpassed for liquid-to-liquid heat transfer. Their innovative design packs maximum performance into a compact and reliable package. We offer copper brazed heat exchangers for use with water, EGW and other common coolants or nickel brazed heat exchangers for high purity and other corrosive coolants.



**BRAZED PLATE LIQUID-TO-LIQUID HEAT EXCHANGERS
TECHNICAL SPECIFICATIONS**

	LL510G12	LL520G12	LL810G12	LL820G12	LL510G14	LL520G14	LL810G14	LL820G14	
Plate Material	AISI 316L Stainless Steel								
Braze Material	Copper 99.9%				Nickel 99.7%				
# of Plates	10	20	10	20	10	20	10	20	
Dry Weight	kg (lb)	1.2 (2.6)	1.7 (3.7)	2.1 (4.9)	2.9 (6.7)	1.2 (2.6)	1.7 (3.7)	2.1 (4.9)	2.9 (6.7)
Size	mm (in)	188 (7.4)	188 (7.4)	310 (12.2)	310 (12.2)	188 (7.4)	188 (7.4)	310 (12.2)	310 (12.2)
Fittings	3/4" MNPT								
Maximum Operating Pressure	31 bar (450 psi)				16 bar (232 psi)				
Maximum Operating Temperature	195°C (383°F)				350°C (662°F)				
Minimum Operating Temperature	-195°C (-319°F)				-195°C (-319°F)				
Maximum Flow Rate	76 lpm (20 gpm)								

**BRAZED PLATE LIQUID-TO-LIQUID
HEAT EXCHANGERS FEATURES**

- Extremely efficient counterflow design allows 90% of the material to be used for heat transfer. The heat exchangers are up to 80-90% smaller than a conventional shell-and-tube design.
- Reliable and rugged heat exchanger with stainless steel sheets brazed together at the edges and at a matrix of contact points.
- Our Copper-brazed units are compatible with water, EGW, and other common coolants. Nickel-brazed units are compatible deionized water, high purity, and corrosive fluids.
- Copper-brazed units can be operated at temperatures of up to 383°F (195° C) and pressures up to 450 psig (31 bar). The Nickel-brazed units can be operated at temperatures of up to 662°F (350°C) and pressures up to 232 psig (16 bar).

NOTICE: This information is being provided for reference purposes only. Boyd Corporation and its affiliates reserve the right to modify or update this information from time-to-time without notice. No representation is made as to the accuracy of and no express or implied warranties are provided for the information or products contained in this data sheet, and no liability shall be assumed for the application or use thereof. For additional information, please contact customerservice@boydcorp.com. © 2019 Boyd Corporation All Rights Reserved

